

	COMPANY	SPIRADRILL	Lo-Dril	WATSON
	MODEL	STUD	DH30	Excadrill-EDT5
Dimensions:	Operational Height (m)	6.1m-7.6m	4.9m-6.7m	5.5m-7.6m
	Operational Height (ft.)	20-25 ft.	16-22 ft.	18-25 ft.
Rotary Drive:	Torque (ft. lbs.)	40,000 ft./lbs.	30,000 ft./lbs.	40,000 ft./lbs.
	Torque (kNm)	54.23 kNm	40.67 kNm	54.23 kNm
Crowd System:	Crowd Force (lbs.)	24,000 lbs.		20,000 lbs.
Winches:	Main Winch Line Pull	15,000 Lbs.	18,000 lbs.	18,000 lbs.
	Main Winch Line Pull (kN)	66.66 kN	80 kN	80 kN
	Auxiliary Winch	8,000 lbs.	5,000 lbs.	
	Auxiliary Winch (kN)	35.56 kN	22.23 kN	
Drilling Data:	Drilling depth (ft)	60 ft.	50 ft.	60 ft.
	Drilling Depth (m)	18.28m	15.24m	18.28m
	Drilling Diameter (m)	1.83m	1.37m	1.83m
	Drilling Diameter (ft.)	72 inches	54 inches	72 inches

Note: Data may vary. The information presented is based on available manufacturer's printed information. We accordingly make no representation with respect to the accuracy or validity of the information, but merely provide it for comparison purposes.